

MySQL Sakai database (2.x and 10.x)

Create a Sakai database with a default character set of UTF-8. Create a user account to which you will assign all permissions.

Use any database name and username you wish and then update your sakai.properties file (or even better, create a local.properties file, which has precedence).

In the example below the database is named "sakaidatabase" and the user account is "sakaiuser".

Excerpt from sakai.properties

```
username@javax.sql.DataSource=sakaiuser  
password@javax.sql.DataSource=sakaipassword
```

```
## MySQL settings  
# vendor@org.sakaiproject.db.api.SqlService=mysql  
# driverClassName@javax.sql.DataSource=com.mysql.jdbc.Driver  
# hibernate.dialect=org.hibernate.dialect.MySQL5InnoDBDialect  
url@javax.sql.DataSource=jdbc:mysql://127.0.0.1:3306/sakaidatabase?useUnicode=true&characterEncoding=UTF-8  
# validationQuery@javax.sql.DataSource=select 1 from DUAL  
# defaultTransactionIsolationString@javax.sql.DataSource=TRANSACTION_READ_COMMITTED
```

```
mysql -u root -p  
Enter password:  
Welcome to the MySQL monitor.  Commands end with ; or \g.  
Your MySQL connection id is 272  
Server version: 5.1.46 MySQL Community Server (GPL)  
  
Copyright (c) 2000, 2010, Oracle and/or its affiliates. All rights reserved.  
This software comes with ABSOLUTELY NO WARRANTY. This is free software,  
and you are welcome to modify and redistribute it under the GPL v2 license  
  
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.  
mysql> create database sakaidatabase default character set utf8;  
Query OK, 1 row affected (0.00 sec)  
  
mysql> grant all on sakaidatabase.* to sakaiuser@'localhost' identified by 'sakaipassword';  
Query OK, 0 rows affected (0.00 sec)  
  
mysql> grant all on sakaidatabase.* to sakaiuser@'127.0.0.1' identified by 'sakaipassword';  
Query OK, 0 rows affected (0.00 sec)  
  
mysql> flush privileges;  
Query OK, 0 rows affected (0.00 sec)  
  
mysql> quit
```